# WHITMORE'S

## **TECHNICAL DATA SHEET**

### BRIGHT KNIGHT™ GOLD 50 CLEANER/DEGREASER

Bright Knight<sup>™</sup> Gold 50 is a blend of all-natural solvent, extracted from orange peels, combined with emulsifiers and petroleum solvent. This combination forms a highly effective degreasing blend for use in removing the toughest industrial greases, asphaltic residues and tar. The special emulsifier formula can be easily rinsed away with water.

Bright Knight<sup>™</sup> Gold 50 can be used full strength for tough jobs or diluted with water as required. The combination of excellent cleaning power and pleasant citrus odor makes it suitable for a wide variety of applications, both indoors and outdoors.

#### **BENEFITS**:

- NATURAL CITRUS BASE eliminates unpleasant odors
- VERSATILE for use in industrial and commercial applications

#### **APPLICATIONS:**

Bright Knight<sup>™</sup> Gold 50 is effective for all industrial applications: parts washing, degreasing concrete and wood floors, equipment cleaning, general degreasing, heavy tar and asphalt accumulations, and drain flushing.

Bright Knight<sup>™</sup> Gold 50 is suitable for use in commercial and residential establishments.

#### Recommended concentration:

Removing tar, asphalt, grease, and carbon: Use undiluted for difficult deposits. Rinse with water.

General commercial cleaning and degreasing: Dilute 4 ounces (half a cup) of Bright Knight<sup>TM</sup> Gold 50 Cleaner to 1 gallon of warm water and apply to equipment, floors, walls, and other soiled surfaces. Rinse with clean water.

Drain Opener: Pour in 8 ounces of Bright Knight<sup>M</sup> 50. Allow 30-60 minutes, and then flush with hot water.

#### CAUTION - COMBUSTIBLE

Keep away from sparks, heat, and open flames. KEEP OUT OF REACH OF CHILDREN.

ASTM #		TYPICAL CHARACTERISTICS
D-2161	Saybolt Viscosity SUS @ 100°F	<32
D-56 (TCC)	Flash Point, °F (°C)	115 (46)
Gardner Method	Density, lb/gal @ 60°F (15.5°C) Specific Gravity, g/cc @ 60°F (15.5°C)	6.84 0.8215
	pH	6.8
	Odor	Citrus

The above are average values. A single test result may vary slightly without affecting performance.

#### PACKAGING



#### THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108 An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • <u>http://www.whitmores.com</u>

Performance Under Pressure Since 1893

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly. Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.