

## **TECHNICAL DATA SHEET**

### **MECHANICS THREAD LOOSENER**

Whitmore's Mechanics Thread Loosener is a fast-acting highly effective penetrating oil. It provides maximum penetration of rust, corrosion, gum and varnish to loosen tightened parts. Mechanics Thread Loosener also acts to displace moisture and provides a light lubricating oil to protect metal parts. Excellent for hard-to-reach applications.

Whitmore's Mechanics Thread Loosener is also available in an aerosol spray container. The solvent propellant has been removed, making Mechanics Thread Loosener environmentally safe and TCLP-SAFE.

#### **BENEFITS:**

- CORROSION INHIBITED protects against rust and corrosion.
- FAST-ACTING quickly frees "frozen" parts.
- DISPLACES MOISTURE leaves a protective coating of light oil.
- PENETRATES AND LUBRICATES minimizes breaking of bolts and stripping of threads
- AVAILABLE IN AN AEROSOL SPRAY lubricates hard-toreach areas.
- GUARDS AGAINST WEAR extends parts life.

#### **APPLICATIONS:**

Mechanics Thread Loosener is an all-purpose light, penetrating oil which is ideal for applications in general maintenance such as loosening rusted or corroded nuts and bolts, stopping squeaks and lubricating pins, valves and hinges.

ASTM#		TYPICAL CHARACTERISTICS
	ISO Grade	32
D-445	Kinematic Viscosity cSt @ 40°C cSt @ 100°C	32 6
D-2161	Saybolt Viscosity SUS @ 100°F SUS @ 210°F	152 44
D-2270	Viscosity Index	100
Gardner Method	Density, lb/gal @ 60°F (15.5°C) Specific Gravity, g/cc @ 60°F (15.5°C)	7.32 0.879
D-92	Flash Point, °F (°C) Cleveland Open Cup	375 (191)
D-92	Fire Point, °F (°C) Cleveland Open Cup	375 (191)
D-2783	Four Ball EP Weld Point, kg	200
D-665	Rust Test Distilled Water Synthetic Sea Water	Pass Pass
D-130	Copper Strip Corrosion 212°F (100°C) @ 3 hr	1B

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

# Pails Aerosol Cans 12 per case

#### THE WHITMORE MANUFACTURING COMPANY

930 Whitmore Drive • P.O. Box 9300 • Rockwall, Texas 75087 • USA • (972) 771-1000 • Fax: (972) 722-2108
An ISO 9001, ISO/TS 16949, and ISO 14001 Registered Company • <a href="http://www.whitmores.com">http://www.whitmores.com</a>
Performance Under Pressure Since 1893

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF TINESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.